

NAD

NAD C 558 Turntable



NAD Electronics has a long history of offering high performance turntables at unbelievably great prices. We continually strive for that sweet spot where you get 90% of the ultimate available performance for only 10% of the price. A product that critical listeners can applaud for its musical quality, and one that almost anybody can afford. This is the NAD C 558.

SOPHISTICATED TECHNOLOGY ▼

While most of the world has focused on digital technology, there has been a quiet revolution of understanding and refinement in the analogue turntable design. On the one hand the task is very simple; spin the platter at precisely 33.3 RPM without any variation, and perfectly track the grooves of the record while giving the cartridge a solid platform that allows all the energy in the record to be translated into stylus motion of the cartridge. We don't want the energy to 'leak' into vibrating the tonearm or the platter; we want it all to become pure musical energy bursting forth from your speakers.

To this end we use a sophisticated power supply that transforms the AC alternating voltage of your wall socket into a pure DC voltage. We then regenerate the DC voltage into a precise AC voltage that powers a precision clock motor to achieve nearly perfect speed consistency and smoothness. The motor is isolated from noise and voltage fluctuations that occur in the raw unfiltered AC mains that can cause instability in the motor. The motor uses a specially developed rubber belt that is flat ground for precision and drives a non-resonant sub platter that is also precisely machined for smooth rotation. This sits in a brass bearing with a hardened steel shaft. All of these parts are carefully developed to work together to provide a remarkably stable and precise rotation of the disc.

Our tonearm also offers a similar level of careful engineering and development. At 9" long it offers low tracking distortion while maintaining rigidity and low mass required to stabilize the cartridge. By allowing VTF and Azimuth adjustment we get precise tracking with low distortion and record wear.

The glass platter and massive plinth combine to extract all the energy from the disc while isolating unwanted external vibrations.

FEATURES & DETAILS

- ▶ Belt Driven Turntable 33/45
- ▶ 10mm Glass Plater with Felt Pad
- ▶ Precision AC Motor
- ▶ Isolated AC Power Supply with Universal Voltage
- ▶ 9" Tonearm with Fixed Head Shell
- ▶ Ortofon OM10 Cartridge Preinsatalled
- ▶ Vertical Tracking Angle and Azimuth Adjustment
- ▶ Rigid MDF Plinth with Rubber Isolation Feet
- ▶ Low Resonance Dustcover
- ▶ Detachable High Quality RCA Cable with separate Ground




QUALITY PARTS AND MATERIALS ▼

The plinth is solid MDF, not the particle board or plastic typically found at this price, and is CNC machined for precision. Our dustcover, too, is heavier than most and made from a non-resonant Perspex with a counter-sprung hinge design that allows the cover to remain in almost any intermediate position from open to closed.

EVERYTHING YOU NEED TO ENJOY VINYL ▼

Listening to vinyl records is an immersive experience. You become as involved in the process as you do in the listening. To a much greater degree than with digital sources, vinyl playback requires solid mechanical precision to extract the music from the medium. A properly played record is a fantastic and rewarding experience, and the NAD C 558 has everything you need to get maximum enjoyment with minimal fuss and expense.



Specifications C 558 ▾

GENERAL SPECIFICATIONS	
Nominal speed	33/45 rpm, manual speed change (78 rpm possible with special pulley)
Speed variance	33rpm: $\pm < 0.50\%$, 45rpm: $\pm < 0.45\%$
Wow and flutter	33rpm: $\pm < 0.15\%$, 45rpm: $\pm < 0.15\%$
Signal to noise	S/N Ratio (mechanical noise): - 40 dB S/N Ratio (electrical noise): -68 dB
Downforce range	0 - 30 mN 0 - 3.0 grams
Supplied counterweight system	Counterweight (black) for cartridges 5 - 12 g
Effective tonearm mass	9.5 g
Effective tonearm length	230 mm
Overhang	18 mm
Power consumption	5 W max/ 0.3W standby
Voltage	Universal switch mode power supply
Voltage	15 V DC/0,8 A, 100-240 V AC, 47 - 63Hz
DIMENSIONS AND WEIGHT	
Dimensions	17 1/8 x 13 3/8 x 4 59/64" (435 x 340 x 125mm)
Net Weight	5,5 kg (turntable) - 1,74 kg (platter)
Shipping Weight	8 kg
Ortofon OM 10 cartridge technical data	
Frequency range	20-22.000Hz
Channel separation	22dB/1kHz
Output voltage	4mV
Recommended load impedance	47kohms/amplifier connection – MM-input
Compliance/stylus type	20 μ m/mN – elliptical
Recommended tracking force	15mN
Weight	5g

* Gross dimensions include feet and rear panel terminals. ** Non-metric measurements are approximate. NAD Electronics will not assume any liability for errors being made by retailers, custom installers, cabinet makers, or other end users based on information contained in this document. Note: Installers should allow a minimum clearance of 55mm for wire/cable management.



NAD Electronics International reserves the right to change specifications or features without notice. NAD is a registered trademark of NAD Electronics International. All rights reserved. No part of this publication may be reproduced, stored, or transmitted in any form whatsoever without the written permission of NAD Electronics International. © 09/17 17-057 NAD Electronics International. www.NADelectronics.com